

1. PRODUCT AND COMPANY IDENTIFICATION

Product name CORAFOAM® PIR FOAM

CAS number Mixture

Product type and use Rigid expanded polyurethane modified polyisocyanurate foam for thermal

insulation

Company DUNA-USA Inc.

4210 FM 1405 Baytown, TX, 77523 USA

1-281-383-3862 info-dunausa@dunagroup.com

In case of emergency call CHEMTREC 1-800-424-9300 (24 HOURS DAY, 7 DAYS A WEEK)

2. HAZARDS IDENTIFICATION

Physical state Solid

Appearance Rigid foam

Emergency overview Low hazard for usual industrial or commercial handling

OSHA regulatory status This product is considered NOT hazardous under OSHA Hazard

Communication Standard (29 CFR 1910.1200).

Potential health effects

Eyes Dust may irritate the eyes.

Skin Nonirritating. May cause irritation only through mechanical abrasion.

Inhalation Dust may irritate the respiratory system.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a

primary route of occupational exposure.

Target organs Inhalation

Skin Eye

Chronic effects Frequent inhalation of dust over a long period of time increases the risk of

developing lung diseases.

Signs and symptoms May cause eye irritation. Itching, redness, burning of skin.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Name	CAS number	%
Rigid expanded polyurethane modified polyisocyanurate foam	not applicable	90 - 100
Cyclopentane	287-92-3	2.5 - 10.0
2-Methylbutane	78-78-4	1 - 2.5



4. FIRST AID MEASURES

First aid procedures

Eye contact Dust in the eyes: Flush thoroughly with water for at least 15 minutes. Get

medical attention if any discomfort continues.

Skin contact Contact with dust: Essentially nonirritating to skin. Wash with soap and

water if mechanical injury occur.

Inhalation If symptoms develop, move to fresh air. Get medical attention if discomfort

develops or persists.

Ingestion Do not induce vomiting. Get medical attention immediately.

5. FIRE-FIGHTING MEASURES

Flammable properties Not flammable by OSHA criteria

Extinguishing media

Suitable extinguishing media

No specific measures are required as this product is a fire extinguishing

medium.

Protection of firefighters

Specific hazards arising from the chemical

Not a fire hazard.

Fire fighting instructions Keep people away. Isolate fire and deny unnecessary entry. Soak

throughly with water to cool and prevent re-ignition. Cool surroundings with water to localize fire zone. Hand held dry chemical or carbon dioxide

extinguisher may be used for small fires.

Fire fighting equipment Wear positive-pressure self contained breathing apparatus (SCBA) and

protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). If protective equipment is not available or not used,

fight fire from a protected location or safe distance.

Specific methods Not applicable.

Hazardous combustion products

Carbon monoxide. Nitrogen oxides.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions No special precautions are necessary beyond normal good hygiene

practices. See Section 8 of the MSDS for additional personal protection

advice when handling this product.

Environmental precautions No specific precautions.

Methods for cleaning up For waste disposal, see Section 13 of the MSDS.



7. HANDLING AND STORAGE

Handling Use work methods which minimize dust production. Use only in well-

ventilated areas. Wear appropriate personal protective equipment. Wash hands after handling. Observe good industrial hygiene practices. Refer to "EXPOSURE CONTROLS AND PERSONAL PROTECTION", Section 8 of the MSDS. No smoking, open flames or sources of ignition in handling and storage area. Fabrication methods which involve cutting into this product may release the blowing agent(s) remaining in the cells. Provide adequate ventilation to assure localized concentrations in release areas are maintained below the lower flammable limit. Good housekeeping and

controlling of dusts are necessary for safe handling of product.

Storage Store away from incompatible materials. Minimize sources of ignition, such

as static build-up, heat, spark or flame. During shipment, storage, installation and use, this material should not be exposed to flame or other

ignition sources. Read and follow manufacturer's recommendations.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Occupational exposure limits

US. ACGIH Threshold Limit Values

 Components
 Type
 Value

 2-Methylbutane (78-78-4)
 TWA
 600 ppm

 Cyclopentane (287-92-3)
 TWA
 600 ppm

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

 Components
 Type
 Value

 2-Methylbutane (78-78-4)
 TWA
 600 ppm

 1770 mg/m³
 1770 mg/m³

 Cyclopentane (287-92-3)
 TWA
 600 ppm

 1720 mg/m³
 1720 mg/m³

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

ComponentsTypeValue2-Methylbutane (78-78-4)TWA600 ppmCyclopentane (287-92-3)TWA600 ppm

Canada. Ontario OELs. (Ministry of Labor - Control of Exposure to Biological or Chemical Agents)

 Components
 Type
 Value

 2-Methylbutane (78-78-4)
 STEL
 2210 mg/m³

 750 ppm
 TWA
 600 ppm

 Cyclopentane (287-92-3)
 TWA
 600 ppm

 1720 mg/m³
 1720 mg/m³

Canada. Quebec OELS. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

 Components
 Type
 Value

 Cyclopentane (287-92-3)
 TWA
 600 ppm 1720 mg/m³

CORAFOAM® PIR FOAM rev_1 Page n. 3 of 8



Engineering controls Provide sufficient ventilation for operations causing dust formation.

Observe occupational exposure limits and minimize the risk of exposure.

Personal protective equipment

Eye/face protection

No special precautions.

Skin protection Gloves, for handling rough edges

Respiratory protection

When engineering controls are not sufficient to lower exposure levels below the applicable exposure limit, use a NIOSH approved respirator for

dusts.

General hygiene considerations

Handle in accordance with good industrial hygiene and safety practice. Routinely wash work clothing and protective equipment to remove

contaminants. Observe any medical surveillance requirements.

Ingestion No precautions necessary due to the physical properties of the material.

Engineering Controls Ventilation

Provide general and/or local exhaust ventilation to control airborne levels

below the exposure guidelines.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Rigid foam

Physical state Solid

Odor Odorless

Odor threshold Not available

Form Foam

pH Not available

Flash point Closed cup: > 300°C (> 572°F)

Auto-ignition temperature > 400°C (> 752°F)

Solubility in water Insoluble

10. STABILITY AND REACTIVITY

Chemical stability Thermally stable at typical use temperatures. See TDS.

Conditions to avoid Avoid temperatures above 260°C (500°F). UV rays may cause

discoloration.

Incompatibility materials Strong acids, strong alkalies and oxidizing agents

Hazardous polymerization Will not occur

Thermal decomposition Decomposition products depend upon temperature, air supply and the

CORAFOAM® PIR FOAM rev_1 Page n. 4 of 8



presence of other materials. Toxic gases are released during decomposition.

11. TOXICOLOGICAL INFORMATION

Toxicological data

Components Test results

2-Methylbutane (78-78-4) Acute Inhalation LC50 Mouse: 450 mg/l 2 Hours

Acute effects Under normal conditions of intended use, this material does not pose a

risk to health.

irritation of eyes.

Repeated dose toxicity Repeated exposures to dusts of this material are not anticipated to result

in systemic toxicity or permanent lung injury; however, excessive

exposures may cause less severe respiratory effects.

12. ECOLOGICAL INFORMATION

Ecotoxicity The product is not classified as environmentally hazardous. Not expected

to be acutely toxic to aquatic organisms

Persistence and degradability

The product is not biodegradable. Surface photodegradation is expected with exposure to sunlight. No appreciable biodegradation is expected.

Mobility in environmental media

The product is insoluble in water. No bioconcentration is expected because of the relatively high molecular weight (MW greater than 1000). In the terrestrial environment, material is expected to remain in the soil. In

the aquatic environment, material is expected to float.

13. DISPOSAL CONSIDERATIONS

Disposal instructions: Disposal recommendations are based on material as supplied. Disposal

must be in accordance with current applicable laws and regulations, and

material characteristics at time of disposal.

14. TRANSPORT INFORMATION

DOT, TDG, IMDG, IATA-ICAO: Not regulated.

15. REGULATORY INFORMATION

US federal regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D): Not regulated.

CORAFOAM® PIR FOAM rev_1 Page n. 5 of 8



CERCLA (Superfund) reportable quantity (lbs) (40 CFR 302.4)

Cyclopentane: 100 2-Methylbutane: 100

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard No Delayed Hazard No Fire Hazard No Pressure Hazard No Reactivity Hazard No

Section 302 extremely hazardous substance (40 CRF 355, Appendix A)

No

Section 311/312 (40 CFR 370)

No

Drug Enforcement Administration (DEA) (21 CFR 1308.11-15)

Not controlled

WHMIS status

Non controlled

Inventory status

Country(s) or region Inventory name On inventory (yes/no)*

Canada Domestic Substances List (DSL) Yes
Canada Non-Domestic Substances List (NDSL) No
United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations

US - California Hazardous Substances (Director's): Listed substance

Cyclopentane (CAS 287-92-3) Listed.

US - Massachusetts RTK - Substance: Listed substance

2-Methylbutane (CAS 78-78-4) Listed. Cyclopentane (CAS 287-92-3) Listed.

US - New Jersey Community RTK (EHS Survey): Reportable threshold

2-Methylbutane (CAS 78-78-4) 500 LBS

US - New Jersey RTK - Substances: Listed substance

CORAFOAM® PIR FOAM rev_1 Page n. 6 of 8



2-Methylbutane (CAS 78-78-4) Listed.

Cyclopentane (CAS 287-92-3) Listed.

US - Pennsylvania RTK - Hazardous Substances: Listed substance

2-Methylbutane (CAS 78-78-4) Listed.

Cyclopentane (CAS 287-92-3) Listed.

California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986)

This product contains no listed substances known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute.


16. OTHER INFORMATION

Label requirements: None

Hazardous Material Information System

1 Health
1 Flammability
0 Reactivity
Protective Equipment

National Fire Protection Association



Notice to reader

HMIS® is a registered trade and service mark of the NPCA

While the information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED DUNA-USA Inc. EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR DUNA-USA Inc. PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE. NO PART OF THIS DATA SHEET MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM, OR BY ANY MEANS, WITHOUT PERMISSION



IN WRITING FROM DUNA-USA Inc. ALL REQUESTS FOR PERMISSION TO REPRODUCE MATERIAL FROM THIS DATA SHEET SHOULD BE DIRECTED TO DUNA-USA Inc.